



	Φίλτρα με Θηλυκό Σπείρωμα BSP (ISO7/1)	Φίλτρα Φλαντζωτά PN16
	Y-Strainer SS316/PTFE with Female Threads BSP (ISO7/1)	Y-Strainer SS316 Flanged PN16
Pmax	800 psi (55 bar)	GENEBRE 2401
Τεχν.Έντυπο Data Sheet	6408xxB 6408xxC	6408xxD
Διάστ.-Size	Κωδικός - Code	Κωδικός - Code
3/8"	640803	-
1/2"	640804	-
3/4"	640805	-
1"	640806	-
1.1/4"	640807	-
1.1/2"	640808	640868
2"	640809	640869
2.1/2"	640810	640870
3"	640811	640871



Μειωτές Πίεσης Ανοξειδωτοι 316/VITON

Direct-Activated Pressure Reducing Valves 316/VITON



	Φλαντζωτοί - Flanged	
Βιδωτοί BSP	JIS 30K	PN25
Threaded BSP	JIS 30K	PN25
GENEBRE	A-Tide Elite	

GENEBRE



Τεχνικό Έντυπο Data Sheet	44235xA	4423xxA	44239xA	4423xxB	4423xxA
Περιοχή Ρύθμισης Pressure Range	1 ÷ 6 bar	1 ÷ 13 bar	0,2 ÷ 1,5 bar	1 ÷ 13 bar	
Διάστ.-Size	Κωδ.-Code	Κωδ.-Code	Κωδ.-Code	Κωδ.-Code	Κωδ.-Code
in					
DN					
1/2"	442354*	442304E1÷3	442394	-	-
3/4"	442355*	442305E1÷3	442395	-	-
1"	442356*	442306E1÷3	442396	442336E1÷3	442316E1÷3
			442397	442338E1÷3	442318E1÷3
			442398	442339E1÷3	442319E1÷3

Ελατήρια

Springs

	"1"	"2"	"3"
	1 - 6 bar Μπλε Blue	4 - 10 bar Μωβ Purple	8 - 13 bar Κόκκινο Red
Διάστ. Size	Κωδ. Code	Κωδ. Code	Κωδ. Code
1/2"	442344	442364	442384
3/4"	442345	442365	442385
1"	442346	442366	442386
1.1/2"	442348	442368	442388
2"	442349	442369	442389

* +Μανόμετρο 602706 / +Pressure gauge 602706