


## ΔΙΑΚΟΠΤΕΣ MINI ΑΡΣ.-ΘΗΛ.

### DESCRIPTION

Mini ball valve Mignon series way ball valve M/F with aluminium lever




2310

### FEATURES

- brass CW617N body, ball, stem.
- ball ground by diamond-tipped tool, chromium plated.
- virgin P.T.F.E. seats with 7° min. tightness angle.
- o-ring stem packing in NBR rubber.
- aluminium lever with red epoxy coating
- matt chrome finishing.
- threading to ISO 228/1.
- PN 10: TEMP. : -20°C ÷ 130°C

### LEADING DIMENSIONS



R	¼"	3/8"	½"
D (mm)	23	23	23
H (mm)	26	27	31
L (mm)	40	41	44
M (mm)	12	12	12
M1 (mm)	10	10	11
F (mm)	6	8	10

### WORKING PREASSURES AT 80°C

PN 10	*	*	*	p.s.i. 150
	1/4"	3/8"	1/2"	

### PRESSURE DROPS

R	¼"	3/8"	½"
Kv	2.2	2.2	5.5

$$\Delta P [\text{mm H}_2\text{O}] = 10.000 \times \left[ \frac{G [\text{m}^3/\text{h}]}{Kv} \right]^2$$